AX-EP-FM1

3 Position Fireman's Switch





Product overview

The AX-EP-FM1 Firemans Switch is designed for use in the event of fire or other emergencies. Usually located at exits to gas plant rooms, units are key operated 3 position latching switches.

A keyguard with plastic window is available.

Features

- 3 Position Switch
- Normal / Off / Extract
- Keyguard and relacement window availabile
- 6A @ 230Vac
- Supplied with two keys
- Hinged cover available

Product specifications

Output Contacts: 1x SPDT

Contact Rating: 6A @ 230Vac

Keys: 2 Keys

Connections: 4x 100mm flying leads


Dimensions: 88mm x 86mm x 50mm (approx.)

Weight: 300 gms


Installation

- Remove the plastic window and check that the side tabs are intact
- 2. Remove the keyplate (2 screws)
- 3. Mount using base as template
- 4. Replace the keyplate
- Fit the blocking pieces and spring and hang the correct key on a pillar
- The pillars can be removed to store an access card

NB. Ensure the correct key is placed in the box as once the window is fitted it can't be removed without breaking the side tabs.



Switch Positions



Order codes

AX-EP-FM1 3 Position fireman's switch

AX-EP-FMKG Key guard

AX-EP-FMW Replacement window for keyguard

AX-EP-FMHC Hinged Cover

© Copyright Annicom 2016. All Rights Reserved