



Product Overview

The AX-POT is Front panel mounted setpoint control for the AX-PI & ET ranges. It allows the adjustment of the setpoint from a remote location. The control is mounted to a single gang plastic front plate.

Products Features

- Designed for the AX-PI & ET ranges
- Manufactured From Flame Retardant ABS

Product Specifications

Material:	VO Rated Flame Retardant ABS Single gang front plate toBS5733
Setpoint Ranges:	-4 to + 4°C, -20 to + 20°C, 0 to + 40°C
Potentiometer:	1 to 11KOhm
Terminals:	Rising Clamp for 0.5-2.5mm 2 Screened Cable
Maximum Cable Length:	100m
Ambient Temperature:	-10°C to +50°C
Dimensions:	85x85x20mm (max.)
Mounting Hole:	10mm hole for potentiometer
Country of Origin:	United Kingdom

Product Order Codes

AX-POT	External Setpoint Control
--------	---------------------------

Installation:

Single Gang Pattress Installation. Screws are included. Two-Core cabling is required for connection.

Connections:

1-	Not Used
2-	Not Used
3-	Wiper common
4-	CW
5-	CCW

Datasheet Contents

Every effort has been taken in the production of this datasheet to ensure accuracy. Annicom Ltd does not accept responsibility for any damage, expense, injury, loss or consequential loss resulting from any errors or omissions. Annicom Ltd has a policy of continuous improvement and reserves the right to change this specification without notice..