

# **Product Overview**

A low cost power supply providing a regulated 24Vdc output from a 230Vac input. The AX-PS-230-24 Power Supply was designed to provide 24Vdc to power the Annicom range of DIN Rail Modules, but has many other uses where a low cost 24Vdc supply is required. The AX-PS-230-24 features output short circuit protection, LED power ON indication and rising clamp screw terminals. The AX-PS-230-24 is designed for mounting on TS35 section DIN Rail.

### Features

- Regulated 24Vdc Output at 1A
- Output Short Circuit Protection
- LED Power Indication

- High Quality Rising Clamp Terminals
- DIN Rail Mounting (TS35)
- Optional Ventilated Metal Enclosure

### **Product Specifications**

Input Suply:	230Vac (+/- 15%)
Input Supply Fuse:	630mA @ 250Vac
Output Supply:	24Vdc (+/-10%)
Output Fuse:	1A
Terminals:	Rising Clamp for 0.5-2.5mm <sup>2</sup> Cable
LED Indication:	ON when Power on
Ambient Temp. Range:	0 to 50'C
Dimensions:	112mm(w) x 92.5mm(h) x 90mm (approx.)
Country of Origin:	United Kingdom

# **Order Codes**

AX-PS-230-24	-	230Vac to 24Vdc Power Supply
АХ-РЅ-230-24-Е	-	230Vac to 24Vdc Power Supply in a ventilated
		metal enclosure


AX-PS-230-24 - Issue 1.1 - Date 04/12/2012

Page 1 of 2



### Connection

Input Fuse: Output Fuse: 630mA Quick Blow 20mm Type 1A Anti Surge 20mm Type



**Enclosure (option)** 



Ventilated Metal Enclosure

Dimensions: 180(l) x 89(w) x 80(h)

Every effort has been taken in the production of this data sheet to ensure it's accuracy. Axio can not, however, accept responsibility for any damage, expense, injury, loss or consequential loss resulting from any errors or omissions. Axio has a policy of continuous improvement and reserves the right to change this specification without notice.

AX-PS-230-24 - Issue 1.1 - Date 04/12/2012