

Product Overview

The AX-TW-9501/2 Wall Mounted Thermostats are a range of units designed for use in greenhouses, breeding areas or other polluted areas. These units provide a switched output based on the average temperature detected along a stainless steel spiral. There are both exposed and concealed setpoint versions and two temperature ranges.

Features



- Two Temperature ranges
- Exposed and Concealed setpoint versions
- 16A @250Vac Switch Rating
- Easy adjustment of setpoint

Product Specifications

Sensitive Element:		Stainless Steel Spiral
Control Range:	-35	-35 to + 35 degC
	-60	+5 to 60 degC
Switch Type:		SDPT Volt Free Contacts
Switch Rating:	C1	16A(3) @ 250Vac
	C2	6A(1) @ 250Vac
Switching Differential:		1 to 2K
Setpoint:	AX-TW-9501	External Setpoint
	AX-TW-9502	Internal setpoint by means of a screwdriver
Ambient range:	Housing	0 to 70 degC
Housing:		ABS
Dimensions:	Housing	110(h) x 75(w) x 59(d)mm
Protection:		IP55
Country of Origin:		Italy

Installation

The AX-TW-9501/2 industrial wall thermostats should be installed by a suitably qualified technician only. The unit operates at mains voltage and should be installed in accordance with all prevailing regulations.



Order Codes

AX-TW-9501-35	Wall Mounted Thermostat exposed setpoint -35 to + 35 deg C
AX-TW-9501-60	Wall Mounted Thermostat exposed setpoint +5 to + 60 deg C
AX-TW-9502-35	Wall Mounted Thermostat concealed setpoint -35 to + 35 deg C
AX-TW-9502-60	Wall Mounted Thermostat concealed setpoint +5 to + 60 deg C